



# STI 23

Edition 1/December 2001

## Interface technical specifications *for France Telecom's network*

*As required by Directive 1999/5/EC*

### InterSAN service access interface characteristics

**Summary:** This document gives a brief description of the technical characteristics of the interfaces used for accessing the InterSAN services.

#### **Warning :**

"Only the French text is authentic; therefore France Telecom accepts no responsibility or liability whatsoever with regard to any information or data referred to in this document".

France Telecom  
6, Place d'Alleray  
75505 Paris Cedex 15  
France  
<http://www.francetelecom.com>

## Notice

Information enclosed in this document is at terminal equipment manufacturers' disposal, pursuant to Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity.

According to Directive 1999/5/EC and specially Article 4.2, France Telecom reserves the right to modify or complement the information contained in this document in order to update the interface technical specifications and to allow the creation of telecommunication terminal equipments capable of using the services provided by the corresponding interfaces.

France Telecom can be held responsible neither for non-operation or poor operation of a terminal equipment, if the equipment complies with this specification, nor for any damage resulting from the use or misuse of the information contained in this document, towards whoever it be.

Provision of these technical specifications results in no transfer of rights, no granting of license on any intellectual property right, belonging to France Telecom.

France Telecom holds exclusive rights on France Telecom brands mentioned in this document.

France Telecom further points out users' attention on the following points:

1. timer values are indicative and can be subject to modification,
2. due to various technical constraints, some services or service options may not be available on some interfaces,
3. the fact that a service not yet commercially open is described in this document can in no case be considered as a binding commitment on France Telecom part to actually open this service.

## Table of contents

<b>1</b>	<b>OVERVIEW OF THE INTERSAN SERVICE</b> .....	<b>1</b>
1.1	MAIN AND EXTENSION LINKS .....	1
1.2	MAIN LINK INTERFACES .....	1
1.3	EXTENSION LINK INTERFACES .....	1
1.4	CUSTOMISED INTERFACES OFFERED.....	1
1.5	HIGH AND LOW BIT RATE RANGES .....	1
<b>2</b>	<b>GENERAL TECHNICAL SPECIFICATIONS</b> .....	<b>2</b>
<b>3</b>	<b>TRIBUTARY INTERFACE CHARACTERISTICS FOR AGREEMENTS WITH LESS THAN 8 LEASED LINKS</b> .....	<b>2</b>
3.1	ESCON, FAST ETHERNET AND STM1 SDH/ATM INTERFACES.....	2
3.2	1062 MBIT/S FIBRE CHANNEL OR GIGA ETHERNET INTERFACES .....	2
<b>4</b>	<b>TRIBUTARY INTERFACE CHARACTERISTICS FOR AGREEMENTS WITH MORE THAN 8 LEASED LINKS</b> .....	<b>3</b>
4.1	ESCON, FAST ETHERNET OR STM1 SDH INTERFACES .....	3
4.2	1062 MBIT/S FIBRE CHANNEL, GIGA ETHERNET OR ETR/CLO INTERFACES .....	3
4.3	1062 MBIT/S ISC INTERFACES.....	4
<b>5</b>	<b>HISTORY</b> .....	<b>4</b>

## **1 OVERVIEW OF THE INTERSAN SERVICE**

The InterSAN service consists of providing one or more point-to-point bidirectional digital leased links between two remote sites in the same town, a town being defined as the whole urban area formed by a town and its suburbs.

The InterSAN service uses wavelength multiplexing equipment, referred to in the rest of this document as EAS (service access equipment).

### **1.1 MAIN AND EXTENSION LINKS**

The first link is called the main link and the following links are called extension links.

The interface type is the same at both ends of a link.

### **1.2 MAIN LINK INTERFACES**

- ESCON<sup>1</sup> interface (200 Mbit/s)
- Fibre Channel interface (1062 Mbit/s)

### **1.3 EXTENSION LINK INTERFACES**

- ESCON interface (200 Mbit/s)
- Fast Ethernet interface (100 Mbit/s)
- STM1 ATM interface (155 Mbit/s)
- STM1 SDH interface (155 Mbit/s)
- Fibre Channel interface (1062 Mbit/s)
- Gigabit Ethernet interface (1000 Mbit/s)

### **1.4 CUSTOMISED INTERFACES OFFERED**

- 8 and 16 Mbit/s External Time Reference/Control Link Oscillator (ETR/CLO) interface
- 1062 Mbit/s single-mode (SM) Inter System Channel (ISC) interface

### **1.5 HIGH AND LOW BIT RATE RANGES**

The links associated with the ESCON, Fast Ethernet, STM1 ATM and STM1 SDH interfaces belong to the low bit rate range.

The links associated with Fibre Channel and Gigabit Ethernet interfaces belong to the high bit rate range.

---

<sup>1</sup> ESCON is an IBM corporation trademark.

## **2 GENERAL TECHNICAL SPECIFICATIONS**

The optical service interface requires 2 single-mode (SM) or multimode (MM) Fibre Optic (FO) cables (input/output) depending on the protocols transmitted.

The data transfer time from a tributary input to a tributary output can reach a maximum of 0.3 ms.

## **3 TRIBUTARY INTERFACE CHARACTERISTICS FOR AGREEMENTS WITH LESS THAN 8 LEASED LINKS**

This chapter defines the interworking between the customer terminal equipment and the EAS for an agreement with less than 8 Leased Links (LL).

This depends on respecting the optical levels. **The customer is responsible for providing any optical attenuators necessary for adapting the optical levels between the EAS and the customer equipment.**

The optical connection uses **ST connector technology**.

### **3.1 ESCON, FAST ETHERNET AND STM1 SDH/ATM INTERFACES**

The optical interface connection is made using 2 **SM** or **MM** FO cables depending on the protocols being transported.

The EAS optical interface transmits at **1310 nm**.

The optical levels must respect the following values:

EAS incoming optical levels	Maximum	-4 dBm
	Minimum	-25 dBm
EAS outgoing optical levels	Maximum	-16 dBm
	Minimum	-20 dBm

### **3.2 1062 MBIT/S FIBRE CHANNEL OR GIGA ETHERNET INTERFACES**

The optical interface connection is made using 2 **MM** fibre optic cables.

The EAS optical interface transmits at **850 nm**.

The optical levels must respect the following values:

EAS incoming optical levels	Maximum	-3 dBm
	Minimum	-14 dBm
EAS outgoing optical levels	Maximum	-4 dBm
	Minimum	-9.5 dBm

## **4 TRIBUTARY INTERFACE CHARACTERISTICS FOR AGREEMENTS WITH MORE THAN 8 LEASED LINKS**

This chapter defines the interworking between the customer terminal equipment and the EAS for an agreement with more than 8 LLs.

This depends on respecting the optical levels. **The customer is responsible for providing any optical attenuators necessary for adapting the optical levels between the EAS and the customer equipment.**

The optical connection uses **SC/PC connector technology**.

### **4.1 ESCON, FAST ETHERNET OR STM1 SDH INTERFACES**

The optical interface connection is made using 2 **SM** or **MM** FO cables depending on the protocols being transported.

The optical interfaces are concentrated at a ratio of 4 per wavelength.

The EAS optical interface transmits at **1310 nm** (1280 to 1350 nm) and receives in the range **1270 to 1380 nm**.

The optical levels must respect the following values:

EAS incoming optical levels	Maximum	-8 dBm
	Minimum	-28 dBm
EAS outgoing optical levels	Maximum	-8 dBm
	Minimum	-15 dBm

### **4.2 1062 MBIT/S FIBRE CHANNEL, GIGA ETHERNET OR ETR/CLO INTERFACES**

The optical interface connection is made using 2 **SM** or **MM** FO cables depending on the protocols being transported.

The EAS optical interface transmits at:

- **1310 nm** (1280 to 1340 nm) and receives in the range **1270 to 1350 nm**
- **850 nm** (830 to 860 nm) and receives in the range **770 to 860 nm**

The optical levels must respect the following values:

EAS incoming optical levels	Maximum	-3 dBm
	Minimum	-17 dBm
EAS outgoing optical levels	Maximum	-3 dBm
	Minimum	-11 dBm

### 4.3 1062 MBIT/S ISC INTERFACES

The Intersystem Channel (ISC) links are IBM ES/9000 large system coupling links which use the Fibre Channel protocol.

The optical interface requires the Open Fiber Control (OFC) protocol (ANSI X3.230-1994) which limits the optical transmission power if the fibre is opened.

The optical interface connection is made using 2 **SM** FO cables.

The EAS optical interface transmits at **1310 nm** (1295 to 1320 nm) and receives in the range **1270 to 1680 nm**.

The optical levels must respect the following values:

EAS incoming optical levels	Maximum	-3 dBm
	Minimum	-20 dBm
EAS outgoing optical levels	Maximum	-3 dBm
	Minimum	-8 dBm

## 5 HISTORY

<b>Edition</b>	<b>Date</b>	<b>Comments</b>
1	December 2001	First version